

Introduction

These installation instructions are provided for the connection and starting procedure of your shaft encoder.

For further informations see our Shaft Encoders Catalogue.

Safety and Operating Instructions

- The incremental shaft encoders of the type RI 58 / RI 59 model series are quality products manufactured in accordance with established electrical engineering standards.
The units have been delivered from the factory in perfect conformance to safety regulations.
To maintain this condition and to ensure trouble-free operation, please observe the technical specifications of this document.
- **Installation and mounting may only be performed by an electrotechnical expert!**
- The units may only be operated within the limits specified by the technical data.
- **Maximum operating voltages must not be exceeded!**
The units are designed complying with VDE 0160, protection class III.
To prevent dangerous structure-borne currents, the equipment has to be run on safety extra-low voltage (SELV) and must be in an area of equipotential bonding.
- **Application: Industrial processes and control systems.**
Overvoltage at the connecting terminals must be limited to the values within overvoltage category II.
- Please avoid shocks to the housing – especially to the encoder shaft – and axial or radial overload to the encoder shaft.
- Maximum accuracy and durability of our shaft encoders is only granted when using suitable couplings.
- The high-quality EMC-specifications are only valid together with standard-type cables and plugs. When using screened cables, the screen must broadly be connected with ground on both ends. Likewise, the voltage-supply cables should entirely be screened. If this is not possible you will have to take appropriate filtering measures.
- Installation environment and wiring are influential on the encoder's EMC: Thus the installer must secure EMC of the whole facility (device).
- Transient peaks on the power supply leads are to be limited by the pre-connected power unit to a maximum of 1000 V.
- In electrostatically threatened areas please take care for neat ESD-protection of plug and connecting cable during installation work.

Mechanical data

Shaft diameter	6 / 6.35 / 7 / 9.52 / 10 / 12 mm	
Absolute max. shaft load	Ø 12 mm	radial 180 N (39 lbs) axial 140 N (30 lbs)
	Ø 7 ... 10 mm	radial 160 N (35 lbs) axial 107 N (24 lbs)
	Ø 6 mm / 6.35 mm	radial 110 N (24 lbs) axial 60 N (13 lbs)
Maximum speed	10,000 RPM	
Torque	≤ 0.5 Ncm (IP 64)	
Moment of inertia	synchro flange 14 gcm ² approx.	
	clamping flange 20 gcm ² approx.	
Protection class	housing/ball bearing IP 50/40, IP 65/64 ¹⁾ , IP 67/67	
Operating temperature	RI 58-O: -10 ... +70 °C / RI 58-T: -25 ... +100 °C	
Storing temperature	RI 58-O: -25 ... +85 °C / RI 58-T: -25 ... +100 °C	
Vibration performance (IEC 68-2-6)	100 m/s ² (10 ... 2,000 Hz)	
Shock resistance (IEC 68-2-27)	1,000 m/s ² (6 ms)	
Connection	1.5 m cable or flange box	
Housing	RI 58: aluminium, RI 59: high-grade steel	
Flange ²⁾	S = synchro flange, K, L = clamping flange, G, Q = square flange, M = synchro clamping flange	
Weight	360 g approx.	
Bearing life	1 × 10 ¹⁰ revolutions (typ.) at 35% of full rated shaft load	
	1 × 10 ⁹ revolutions (typ.) at 75% of full rated shaft load	
	1 × 10 ⁸ revolutions (typ.) at 100% of full rated shaft load	
¹⁾ no standing water allowed at the shaft entrance or at the ball bearing		
²⁾ S, L: use threads M4 for fastening K: use threads M3 for fastening M: use threads 10-32 UNF for fastening		

Electrical data

General design	as per DIN VDE 0160, protection class III, contamination level 2, overvoltage class II					
Screening	connected to housing					
Noise emission	as per EN 50081-2 (edition 1993)					
Noise immunity	as per EN 50082-2 (edition 1995)					
Power consumption	40 mA (5 V DC), 30 mA (24 V DC), 60 mA (10 V DC)					
Supply voltage U _B	5 V DC (SELV) ±10%		10 ... 30 V DC (SELV)			
Output circuit ¹⁾	PP	PP	RS422	PP	PP compl.	RS422
Code letter	K	D	R, T	K	I	R
Output load [mA]	±10	±30	±30	±30	±30	±30
Output level [V]	High	≥2.5	≥2.5	≥2.5	U _B -3	U _B -3
	Low	≤0.5	≤0.5	≤0.5	≤2	≤2
Pulse rise time [ns]	250	100	100	2000	2000	100
Max. pulse frequency [kHz]	300	300	300	200	200	300
Pole protection of U _B	yes	no	no	yes	yes	yes
Short circuit proof	yes	1 chn.	1 channel	yes	yes	yes
Pulse duty factor	1 : 1					
Pulse width error	± 25° electrical					
Phase shift	90° (distance from Channel A to B is at least 0.45 µs, at 300 kHz)					
Pulse shape	rectangular					
Alarm output	Open Collector, NPN (5 mA, 24 V max with U _B =5VDC; 5 mA, 32 V max. with U _B =10...30 VDC)					
¹⁾ PP=Push-pull; PP compl.=Push-pull complementary; RS422=Line driver						

